


## Nakrętka złączna do prętów gwintowanych DIN 6334



index	Symbol	Średnica gwintu [mm]	Grubość nakrętki [mm]	Opak. (szt.)
2110	M6/18	M6	18	50
2111	M8/24	M8	24	50
2112	M10/30	M10	30	50
2113	M12/36	M12	36	50
2115	M16/48	M16	48	25

## Nakrętka sześciokątna PN: 82144 DIN-934



index	Symbol	Średnica gwintu [mm]	Grubość nakrętki [mm]	Opak. (szt.)
2121	M6	M6	5	200
2122	M8	M8	6,5	100
2123	M10	M10	8	100
2124	M12	M12	10	50
2126	M16	M16	13	25

## Nakrętka kołpakowa



index	Symbol	Średnica gwintu [mm]	Opak. (szt.)
2130	M6	M6	100
2131	M8	M8	100
2132	M10	M10	50
2133	M12	M12	50
2134	M16	M16	25

## Nakrętki samo-kontrolujące ocynkowane

Posiadają wkładkę poliamidową zabezpieczającą przed odkręcaniem.

**Charakterystyka:**

- powierzchnia ocynkowana
- norma DIN 985



index	Symbol	Średnica gwintu [mm]	Opak. (szt.)
2141	M6	M6	100
2142	M8	M8	100
2143	M10	M10	50
2144	M12	M12	50
2146	M16	M16	25

## Podkładka okrągła zgrubna DIN 125



index	Symbol	Średnica wewnętrzna [mm]	Średnica zewnętrzna [mm]	grubość [mm]	Opak. (szt.)
2151	M6	6,6	12	1,6	200
2152	M8	9,0	16	1,6	100
2153	M10	11,0	20	2,0	100
2154	M12	13,5	24	2,5	50
2156	M16	17,5	30	3,0	25

## Podkładka okrągła zgrubna powiększona DIN 9021



index	Symbol	Średnica wewnętrzna [mm]	Średnica zewnętrzna [mm]	grubość [mm]	Opak. (szt.)
2161	M6	6,4	18	1,6	200
2162	M8	8,4	22	2,0	100
2163	M10	10,5	28	2,5	100
2164	M12	13,0	34	3,0	50
2166	M16	17,0	40	5,0	25